



Sealant Remover is a ready to use and rapid spray based on hydrocarbons for removing cured silicone and ms polymers.

Features & Benefits

- Improves the adhesion of various hybrid (MS, SMX) and silicone based adhesives, sealants and tapes
- Fast-working
- Does not drip
- Specifically for silicones and MS polymers

Applications

- Removal of old silicone residue, spilled silicone or spilled MS polymers from different kind of surfaces.
- Removes all residue of spilled silicone.

Technical data

Basis	Based on hydrocarbons
Consistency	Liquid
Density	Ca. 0,87 g/ml
Viscosity	1400 +/- 600 Poise
Solubility in water	Not soluble
Solubility in other	Soluble in hydrocarbons
Application temperature	5 °C → 30 °C

* These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. ** This information relates to fully cured product.



Product description

Sealant Remover is a ready to use and rapid spray based on hydrocarbons for removing cured silicone and ms polymers.

Properties

- Fast acting
- Does not drip
- Specifically for silicones and MS polymers

Applications

- Removal of old silicone residue, spilled silicone or spilled MS polymeres from different kind of surfaces.
- Removes all residue of spilled silicone.

Shelf life

3 years in unopened packaging in a dry and cool environment at temperatures between +5°C and +25°C.

Substrates

Substrates: coated metals, ceramic tiles, laminated plate, painted surfaces, glass, aluminium, some synthetic materials (NOT nylon and PMMA)

Nature: dry

Application method

Application method: Apply on dry ground and dry conditions. Remove hard putty first with a knife. Shake the canister thoroughly and apply Sealant Remover on the surface to be cleaned. Leave to work for at least 10 min. Wipe dry with a clean cloth. Repeat if necessary. Wash thoroughly with water to avoid surface degradation.